

Procedures: Functions and subroutines

Victor Eijkhout, Susan Lindsey

Fall 2022

last formatted: October 19, 2022

Procedure basics

1. Procedures in contains clause

Simplest way of defining procedures:
in `Contains` part of main program.

```
Program foo
  < declarations >
  < executable statements >
  Contains
    < procedure definitions >
End Program foo
```

Two types of procedures: functions and subroutines. More later.

2. Subroutines

```
subroutine foo()  
  implicit none  
  print *, "foo"  
  if (something) return  
  print *, "bar"  
end subroutine foo
```

- `Subroutine` is like a `void` function.
- Same structure as main program.
- Ends at the end, or when `return` is reached.
- Note: `return` does not return anything:
indicates return from the procedure.
- Invoked with

```
call foo()
```

3. Subroutine with argument

Code:

```
program printone
  implicit none
  call printint(5)
contains
  subroutine printint(invalue)
    implicit none
    integer :: invalue
    print *,invalue
  end subroutine printint
end program printone
```

Output:

5

Arguments types are defined in the body, not the header

4. Subroutine can change argument

Code:

```
program addone
  implicit none
  integer :: i=5
  call addint(i,4)
  print *,i
contains
  subroutine addint(inoutvar,addendum)
    implicit none
    integer :: inoutvar,addendum
    inoutvar = inoutvar + addendum
  end subroutine addint
end program addone
```

Output:

9

Parameters are always 'by reference'!

Function vs Subroutine

Subroutines can only 'return' results through their parameters.

Functions have an actual return result returned by assigning to function name

5. Function example

Code:

```
program plussing
  implicit none
  integer :: i
  i = plusone(5)
  print *,i
contains
  integer function plusone(invalue)
    implicit none
    integer :: invalue
    plusone = invalue+1 ! note!
  end function plusone
end program plussing
```

Output:

6

- The function name is a variable
- ... that you assign to.

6. Function definition and usage

- `subroutine` VS `function`:
compare `void` functions vs non-void in C++.
- Function header:
Return type, keyword `function`, name, parameters
- Function body has statements
- Result is returned by assigning to the function name
- Use: $y = f(x)$

7. Why a 'contains' clause?

```
Program NoContains
  implicit none
  call DoWhat()
end Program NoContains

subroutine DoWhat(i)
  implicit none
  integer :: i
  i = 5
end subroutine DoWhat
```

Warning only, crashes.

```
Program ContainsScope
  implicit none
  call DoWhat()
contains
  subroutine DoWhat(i)
    implicit none
    integer :: i
    i = 5
  end subroutine DoWhat
end Program ContainsScope
```

Error, does not compile

8. Why a 'contains' clause, take 2

Code:

```
Program NoContainTwo
  implicit none
  integer :: i=5
  call DoWhat(i)
end Program NoContainTwo

subroutine DoWhat(x)
  implicit none
  real :: x
  print *,x
end subroutine DoWhat
```

Output:

```
nocontain2.F90:15:16:

    15 |   call
        |   DoWhat(i)
        |
        |   1
Warning: Type
mismatch in
argument 'x' at
(1); passed
INTEGER(4) to
REAL(4)
[-Wargument-mismatch]
7.00649232E-45
```

At best compiler warning if all in the same file

Exercise 1

Write a program that asks the user for a positive number; negative input should be rejected. Fill in the missing lines in this code fragment:

Code:

```
program readpos
  implicit none
  real(4) :: userinput
  print *, "Type a positive number:"
  userinput = read_positive()
  print *, "Thank you for", userinput
contains
  real(4) function read_positive()
    implicit none
    !! ...
  end function read_positive
end program readpos
```

Output:

```
Type a positive
      number:
No, not  -5.00000000
No, not   0.00000000
No, not  -3.14000010
Thank you for
      2.48000002
```

9. Procedure arguments

Arguments are declared in procedure body:

```
subroutine f(x,y,i)
  implicit none
  integer,intent(in) :: i
  real(4),intent(out) :: x
  real(8),intent(inout) :: y
  x = 5; y = y+6
end subroutine f
! and in the main program
call f(x,y,5)
```

declaring the 'intent' is optional, but highly advisable.

10. Fortran nomenclature

The term dummy argument is what Fortran calls the parameters in the procedure definition:

```
subroutine f(x) ! 'x' is dummy argument
```

The arguments in the procedure call are the actual arguments:

```
call f(x) ! 'x' is actual argument
```

11. Parameter passing

- Everything is passed by reference.
Don't worry about large objects being copied.
- Optional intent declarations:
Use `in`, `out`, `inout` qualifiers to clarify semantics to compiler.

12. Intent checking

Compiler checks your intent against your implementation. This code is not legal:

```
subroutine ArgIn(x)
  implicit none
  real,intent(in) :: x
  x = 5 ! compiler complains
end subroutine ArgIn
```


13. Why intent checking?

Self-protection: if you state the intended behaviour of a routine, the compiler can detect programming mistakes.

Allow compiler optimizations:

```
x = f()  
call ArgOut(x)  
print *,x
```

Call to f removed

```
do i=1,1000  
  x = ! something  
  y1 = .... x ....  
  call ArgIn(x)  
  y2 = ! same expression as y1
```

y2 is same as y1 because x not changed

(May need further specifications, so this is not the prime justification.)

Exercise 2

Write a subroutine `trig` that takes a number α as input and passes $\sin \alpha$ and $\cos \alpha$ back to the calling environment.

Exercise 3

Take your prime number testing function `is_prime`, and use it to write a program that prints multiple primes:

- Read an integer `how_many` from the input, indicating how many (successive) prime numbers should be printed.
- Print that many successive primes, each on a separate line.
- (Hint: keep a variable `number_of_primes_found` that is increased whenever a new prime is found.)

Turn it in!

- If you have compiled your program, do:
`coe_primef yourprogram.F90`
where 'yourprogram.F90' stands for the name of your source file.
- Is it reporting that your program is correct? If so, do:
`coe_primef -s yourprogram.F90`
where the `-s` flag stands for 'submit'.
- If you don't manage to get your code working correctly, you can submit as incomplete with
`coe_primef -i yourprogram.F90`
- Use the `-d` debug flag for more information.

14. Saved values

Local variable is initialized only once,
second time it uses its retained value.

Code:

```
integer function maxof2(i,j)
  implicit none
  integer,intent(in) :: i,j
  integer :: max=0
  if (i>max) max = i
  if (j>max) max = j
  maxof2 = max
end function maxof2
```

Output:

```
Comparing:  1   3
           3
Comparing: -2  -4
           3
```